



PREDATOR[®]
PURSUIT OF PERFORMANCE TIRES

PREDORTIRES.COM

PURSUIT OF PERFORMANCE

WWW.PREDATORTIRES.COM

Predator Tires is an American brand driven by the Pursuit of Performance—built for drivers who live for adventure and demand the best. Designed in the USA, our tires reflect the power, precision, and pride of American engineering. With bold styling, sharp handling, and rock-solid durability, our lineup is made to conquer rugged trails, haul heavy loads, and command city streets. Predator Tires—performance driven by American grit.

Our team of passionate engineers and enthusiasts works closely with drivers and dealers to stay ahead of the curve, designing tires that combine head-turning style with unrelenting reliability. We manufacture our products in world-class facilities across Southeast Asia, partnering with top-tier producers who share our obsession with quality and toughness. Leveraging cutting-edge technology, premium materials, and advanced production methods, we ensure every

tire meets the highest global standards for safety and performance. These trusted partnerships enable us to deliver the exceptional quality and value American drivers expect from a brand rooted in the USA.

Unleash your drive with Predator Tires. Explore our lineup today and experience bold performance that powers every journey.



NEW MUTANT X-MT
MAXIMUM TRACTION MUD TIRE



NEW MUTANT X-RT
RUGGED-TERRAIN TIRE



NEW MUTANT RT TRAIL
RUGGED-TERRAIN TIRE



NEW MUTANT X-AT
ALL-TERRAIN TIRE



NEW MUTANT ARCTIC
LIGHT TRUCK WINTER TIRE



ComPtrax PRI R/S
ALL-SEASON ULTRA HIGH PERFORMANCE



ComPtrax PRI Sport
ULTRA-HIGH PERFORMANCE SUMMER TIRE



BOULEVARD G/T
ALL-SEASON TOURING TIRE(WW)



BOULEVARD G/T
ALL-SEASON TOURING TIRE(RWL)



STEEL PAYLOAD
HIGHWAY TRAILER TIRE



Conquer any challenge with the New Mutant X-MT, the most aggressive tire in the lineup. Its dynamic tread pattern and high void ratio effortlessly evacuate mud, dirt, snow, sand, and rocks for constant traction.



Deep tread blocks and massive side lugs deliver superior grip, puncture resistance, and confidence on harsh terrain. On pavement, the variable three-pitch tread pattern minimizes noise and vibration. Built for rock crawling, mud bogs, and heavy loads, the X-MT is durable and reliable.





NEW MUTANT X-MT

Maximum Traction Mud Tire



*Ratings are on a scale of 1-10



- High void-to-lug ratio for extreme off-road conditions: This design keeps the tread clear and provides superior traction in mud, snow, sand, and rocky terrain.
- Staggered shoulder lugs: These lugs enhance grip and biting edge on rocky terrain.
- Deep tread depth: This provides better off-road capability, hydroplaning resistance, and a longer tread life.
- Deep siping in the tread blocks: This improves grip and braking performance in winter and on wet surfaces.
- Mud and stone ejectors: These features help to shed mud and prevent stones from drilling into the tire.
- Advanced "X" tread pattern: This design maximizes traction in any off-road terrain.
- Aggressive "X-TREME SPIKE" X-MT dual sidewall design: This design offers added off-road traction, sidewall armor, and a unique aesthetic.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
17"	LT265/70R17	10PR 121/118Q	NPRXMT01	8J	7.0-9.0	31.65	10.71	18.2	BLK
	LT285/70R17	10PR 121/118Q	NPRXMT02	8 1/2J	7.5-9.5	32.76	11.50	18.2	BLK
	33X12.50R17LT	10PR 120Q	NPRXMT03	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R17LT	10PR 121R	NPRXMT04	10J	8.0-10.5	34.52	12.50	20.2	BLK
18"	LT275/70R18	10PR 125/122R	NPRXMT05	8J	7.0-9.0	33.19	10.98	18.2	BLK
	33X12.50R18LT	10PR 118Q	NPRXMT06	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R18 LT	10PR 123R	NPRXMT07	10J	8.5-11.0	34.52	12.50	20.2	BLK
20"	LT275/55R20	10PR 120/117Q	NPRXMT08	8 1/2J	8.0-9.5	31.89	11.18	18.2	BLK
	LT285/55R20	10PR 122/119Q	NPRXMT09	9J	8.5-10.0	32.36	11.69	20.2	BLK
	33X11.50R20LT	10PR 118Q	NPRXMT10	9J	8.0-10.5	32.52	11.42	20.2	BLK
	33X12.50R20LT	10PR 114Q	PRXMT11	10J	8.5-11.0	32.52	12.50	20.2	BLK
	33X12.50R20LT	12PR 119Q	PRXMT12	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R20LT	10PR 121Q	PRXMT13	10J	8.5-11.0	34.52	12.50	20.2	BLK
	35X12.50R20LT	12PR 125Q	PRXMT14	10J	8.5-11.0	34.52	12.50	20.2	BLK
37X13.50R20 LT	12PR 128Q	NPRXMT15	11J	9.5-12.0	36.52	13.58	20.2	BLK	
22"	33X12.50R22LT	10PR 109R	PRXMT16	10J	10.0-12.0	32.52	12.45	20.2	BLK
	33X12.50R22LT	12PR 114Q	PRXMT17	10J	10.0-12.0	32.52	12.45	20.2	BLK
	35X12.50R22LT	10PR 117R	PRXMT18	10J	8.5-11.0	34.52	12.50	20.2	BLK
	35X12.50R22LT	12PR 121Q	PRXMT19	10J	8.5-11.0	34.52	12.50	20.2	BLK
	37X13.50R22 LT	12PR 128Q	NPRXMT20	11J	9.5-12.0	36.52	13.58	20.2	BLK

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
24"	33X13.50R24 LT	12PR 113Q	NPRXMT21	12 1/2J	11.5-12.5	32.52	13.58	20.2	BLK
	35X13.50R24LT	12PR 116Q	NPRXMT22	12J	11.5-13.5	34.52	13.44	20.2	BLK
	37X13.50R24LT	12PR 124Q	NPRXMT23	11J	9.5-12.0	36.52	13.58	20.2	BLK
26"	37X13.50R26LT	12PR 117Q	NPRXMT24	11J	10.5-13.0	36.52	13.44	20.2	BLK
30"	42X16.50R30LT	10PR 126Q	NPRXMT25	15J	14.5-16.0	41.54	16.57	20.9	BLK
	44X16.50R30LT	10PR 128Q	NPRXMT26	15J	14.0-16.0	43.50	16.57	20.9	BLK



*Every effort has been made to verify the accuracy of the listed information.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

Dominate any terrain with the New Mutant X-RT, engineered for lifted trucks, SUVs, and work and tow rigs. The New Mutant X-RT sets the bar for rugged-terrain tires with its innovative hybrid design that combines the aggressive off-road traction of a mud-terrain tire with the extended tread life and highway stability of an all-terrain tire.



The New Mutant X-RT is the perfect choice for drivers who demand both on-road comfort and off-road capability. Whether you're towing a heavy load, hauling gear, conquering trails, or simply cruising, this versatile tire delivers the perfect combination of traction, durability, and long-lasting performance.





NEW MUTANT X-RT

Rugged-Terrain Tire



*Ratings are on a scale of 1-10


- **Optimized Void-to-Lug Ratio:** This design enhances off-road traction in mud, snow, sand, and rocky terrain by allowing for better self-cleaning of the tread.
- **Deep Tread Depth:** Provides increased off-road capability, improved hydroplaning resistance, and extends the tire's lifespan.
- **Staggered Shoulder Lugs:** These lugs offer a biting edge for superior grip on rocky surfaces.
- **Mud and Stone Ejectors:** Located between the shoulder lug blocks, these features help shed mud and prevent stones from getting lodged in the tread.
- **Advanced "X" Tread Pattern with Pitch Variation:** This design reduces road noise for a quieter highway ride, enhancing comfort for drivers and passengers.
- **Aggressive "TALON" X-RT Dual Sidewalls:** This design not only provides additional off-road traction and sidewall protection but also offers drivers a unique visual customization option.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
14"	LT175/70R14 (EQUIVALENT T024X7.00R14LT)	6PR 95/93 Q	PRXRT48	5J	4.5-6.0	23.70	6.97	16.0	BLK
	16"	265/70R16	112 T	PRXRT51R	8J	7.0-9.0	30.63	10.71	13.2
17"	265/65R17	116T XL	PRXRT49R	8J	7.5-9.5	30.55	10.71	13.2	RWL
	LT265/70R17	10PR 121/118Q	PRXRT42	8J	7.0-9.0	31.65	10.71	16.5	BLK
	LT285/70R17	10PR 121/118Q	PRXRT43	8 1/2J	7.5-9.5	32.76	11.50	16.5	BLK
	LT305/65R17	10PR 121/118Q	PRXRT01	9J	9.0-11.0	32.60	12.24	18.6	BLK
	33X12.50R17LT	10PR 120Q	PRXRT05	10J	8.5-11.0	32.52	12.50	18.6	BLK
	35X12.50R17LT	10PR 121R	PRXRT32	10J	8.0-10.5	34.52	12.50	18.6	BLK
	37X12.50R17 LT	8PR 124Q	PRXRT44	10J	8.0-10.5	36.52	12.50	19.1	BLK
	37X12.50R17 LT	10PR 128Q	PRXRT45	10J	8.0-10.5	36.52	12.50	19.1	BLK
37X13.50R17 LT	10PR 128Q	PRXRT46	11J	9.0-11.5	36.52	13.58	19.1	BLK	
18"	265/60R18	114S XL	PRXRT50R	8J	7.5-9.5	30.51	10.71	13.2	RWL
	LT275/70R18	10PR 125/122Q	PRXRT34	8J	7.0-9.0	33.19	10.98	16.5	BLK
	LT305/60R18	10PR 121/118Q	PRXRT02	9J	9.0-11.0	32.40	12.24	18.6	BLK
	33X12.50R18LT	10PR 118Q	PRXRT06	10J	8.5-11.0	32.52	12.50	18.6	BLK
35X12.50R18LT	10PR 123R	PRXRT33	10J	8.5-11.0	34.52	12.50	18.6	BLK	
20"	LT275/55R20	10PR 120/117Q	PRXRT03	8 1/2J	8.0-9.5	31.89	11.18	18.6	BLK
	LT275/65R20	10PR 126/123R	PRXRT35	8J	8.0-9.5	34.09	10.98	16.5	BLK

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
20"	LT285/55R20	10PR 122/119Q	PRXRT04	9J	8.5-10.0	32.36	11.69	18.6	BLK
	LT305/55R20	12PR 125/122S	PRXRT36	9 1/2J	9.0-11.0	33.23	12.44	16.5	BLK
	33X11.50R20LT	10PR 118Q	PRXRT07	9J	8.0-10.5	32.52	11.42	18.6	BLK
	33X12.50R20LT	10PR 114Q	PRXRT08	10J	8.5-11.0	32.52	12.50	18.6	BLK
	33X12.50R20LT	12PR 119Q	PRXRT09	10J	8.5-11.0	32.52	12.50	18.6	BLK
	33X13.50R20LT	12PR 120Q	PRXRT12	11J	9.5-12.0	32.52	13.58	20.4	BLK
	35X12.50R20LT	10PR 121Q	PRXRT10	10J	8.5-11.0	34.52	12.50	18.6	BLK
	35X12.50R20LT	12PR 125Q	PRXRT11	10J	8.5-11.0	34.52	12.50	18.6	BLK
	35X13.50R20LT	12PR 126Q	PRXRT13	11J	9.5-12.0	34.52	13.58	20.4	BLK
	37X12.50R20 LT	12PR 128Q	PRXRT37	10J	8.5-11.0	36.52	12.50	19.1	BLK
	37X13.50R20 LT	12PR 128Q	PRXRT38	11J	9.5-12.0	36.52	13.58	19.1	BLK
	38X15.50R20LT	10PR 128Q	PRXRT14	12 1/2J	11.0-14.0	37.52	15.54	20.4	BLK
	40X13.50R20LT	10PR 128Q	PRXRT52	11J	9.0-11.5	39.52	13.58	20.4	BLK
	40X15.50R20LT	12PR 128Q	PRXRT15	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK
	22"	33X12.50R22LT	10PR 109Q	PRXRT16	10J	10.0-12.0	32.52	12.45	18.6
33X12.50R22LT		12PR 114Q	PRXRT17	10J	10.0-12.0	32.52	12.45	18.6	BLK
33X13.50R22LT		12PR 116Q	PRXRT26	11J	10.5-12.0	32.52	13.58	20.4	BLK
35X12.50R22LT		10PR 117Q	PRXRT18	10J	8.5-11.0	34.52	12.50	18.6	BLK
35X12.50R22LT		12PR 121Q	PRXRT19	10J	8.5-11.0	34.52	12.50	18.6	BLK
35X13.50R22LT		12PR 122Q	PRXRT27	11J	10.5-12.0	34.52	13.58	20.4	BLK

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
22"	37X13.50R22 LT	12PR 128Q	PRXRT39	11J	9.5-12.0	36.52	13.58	19.1	BLK
	40X15.50R22LT	12PR 128Q	PRXRT20	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK
24"	33X13.50R24LT	10PR 109Q	PRXRT28	12J	11.5-12.5	32.52	13.58	20.4	BLK
	35X13.50R24LT	12PR 116Q	PRXRT21	12J	11.5-13.5	34.52	13.44	20.4	BLK
	37X13.50R24 LT	12PR 124Q	PRXRT40	11J	9.5-12.0	36.52	13.58	19.1	BLK
26"	40X15.50R24LT	12PR 128P	PRXRT22	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK
	35X13.50R26LT	10PR 118Q	PRXRT30	12 1/2J	11.5-12.5	34.52	13.58	20.4	BLK
	37X13.50R26LT	12PR 117Q	PRXRT41	11J	10.5-13.0	36.52	13.44	19.1	BLK
	38X15.50R26LT	12PR 126P	PRXRT31	13 1/2J	13.0-14.0	37.52	15.54	20.4	BLK
28"	40X15.50R26LT	10PR 126P	PRXRT23	12 1/2J	12.5-14.5	39.52	15.43	20.4	BLK
	40X15.50R28LT	10PR 126P	PRXRT24	13 1/2J	13.0-14.0	39.52	15.54	20.4	BLK
	42X15.50R28LT	10PR 128P	PRXRT25	13 1/2J	12.5-14.5	41.52	15.43	20.4	BLK

*Every effort has been made to verify the accuracy of the listed information.
Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



Introducing the New Mutant RT Trail, the newest hybrid off-road tire in the series. It seamlessly blends the rugged capability of the X-RT with the mud-terrain mastery of the X-MT.

Built for adventure seekers who crave both on-road comfort and off-road dominance, the New Mutant RT Trail delivers the perfect balance of performance. Conquer challenging trails with confidence, knowing you have a tire that won't back down.

Engineered for everyday adventure, the New Mutant RT Trail is ideal for drivers who demand top-tier mud-terrain performance without sacrificing on-road comfort. Whether it's your daily driver or your weekend trail rig, this tire is built to handle anything you throw its way.





NEW MUTANT RT TRAIL

Rugged Terrain Tire



Off-Road Performance



Dry Performance



Ride Comfort



Wet Performance



Winter Performance



Quiet Ride



- Optimized void-to-lug ratio for extreme off-road conditions provides unparalleled traction in mud, snow, sand, and rocky terrain.
- Advanced tread pattern and pitch variation tame road noise for a smoother highway ride and increase comfort for drivers and passengers.
- Thick and stylish 3-dimensional sidewall and shoulder lugs that look good and provide puncture and impact resistance on the most rugged terrain.
- Deep, multi-functional tread grooves and siping provide enhanced traction in a wide variety of road conditions.
- An advanced all-terrain tread compound featuring increased tread life and improved on- and off-road traction.



WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
17"	LT235/80R17	10PR 120/117Q	PRRT03R	6 1/2J	6.0-8.0	31.81	9.25	17.4	RWL	-
	LT235/80R17	10PR 120/117Q	PRRT03	6 1/2J	6.0-8.0	31.81	9.25	17.4	BLK	-
	LT245/75R17	10PR 121/118Q	PRRT04	7J	6.5-8.0	31.50	9.76	17.4	BLK	-
	LT265/70R17	10PR 123/120Q	PRRT05	8J	7.0-9.0	31.65	10.71	16.5	BLK	-
	LT285/70R17	10PR 126/123Q	PRRT06R	8 1/2J	7.5-9.5	32.76	11.50	16.5	RWL	-
	LT285/70R17	10PR 126/123Q	PRRT06	8 1/2J	7.5-9.5	32.76	11.50	16.5	BLK	-
	33X12.50R17LT	10PR 120Q	PRRT07	10J	8.5-11.0	32.52	12.50	18.5	BLK	-
	35X11.50R17LT	10PR 128Q	PRRT47	9J	7.5-10.0	34.52	11.42	18.5	BLK	-
40X13.50R17LT	8PR128Q	PRRT50	11J	9.0-11.5	39.52	13.58	18.5	BLK	-	
18"	LT275/65R18	10PR 123/120Q	PRRT09	8J	8.0-9.5	32.09	10.98	16.5	BLK	-
	LT275/70R18	10PR 125/122R	PRRT10	8J	7.0-9.0	33.19	10.98	16.5	BLK	-
	33X12.50R18LT	10PR 118Q	PRRT11	10J	8.5-11.0	32.52	12.50	18.5	BLK	-
	35X12.50R18LT	10PR 123R	PRRT12	10J	8.5-11.0	34.52	12.50	18.5	BLK	-
20"	275/55R20	117T XL	PRRT13	8 1/2J	7.5-9.5	31.89	11.18	13.6	BLK	-
	275/60R20	115T	PRRT15	8J	7.5-9.5	32.99	10.98	13.6	BLK	-
	285/55R20	116T XL	PRRT17	9J	8.0-10.0	34.09	10.98	13.6	BLK	-
	305/55R20	116R	PRRT20	9 1/2J	8.5-11.0	33.23	12.44	13.6	BLK	-
	LT275/55R20	10PR 120/117S	PRRT14	8 1/2J	8.0-9.5	31.89	11.18	16.5	BLK	EV
	LT275/60R20	10PR 123/120S	PRRT53	8J	8.0-9.5	32.99	10.98	16.5	BLK	EV
LT275/65R20	10PR 126/123S	PRRT16	8J	8.0-9.5	34.09	10.98	16.5	BLK	EV	

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
20"	LT285/55R20	10PR 122/119S	PRRT18	9J	8.5-10.0	32.36	11.69	16.5	BLK	-
	LT285/65R20	10PR 127/124S	PRRT19	8 1/2J	8.5-10.0	34.57	11.50	16.5	BLK	EV
	LT305/55R20	12PR 125/122Q	PRRT21	9 1/2J	9.0-11.0	33.23	12.44	16.5	BLK	-
	33X11.50R20LT	10PR 118Q	PRRT46	9J	8.0-10.5	32.52	11.42	16.5	BLK	-
	33X12.50R20LT	10PR 114Q	PRRT01	10J	8.5-11.0	32.52	12.50	18.5	BLK	-
	33X12.50R20LT	12PR 119Q	PRRT02	10J	8.5-11.0	32.52	12.50	18.5	BLK	-
	35X11.50R20LT	10PR 124Q	PRRT22	9J	8.0-10.5	34.52	11.42	16.5	BLK	-
	35X12.50R20LT	10PR 117Q	PRRT23	10J	8.5-11.0	34.52	12.50	18.5	BLK	-
	35X12.50R20LT	12PR 125Q	PRRT24	10J	8.5-11.0	34.52	12.50	18.5	BLK	-
	35X13.50R20LT	12PR 126Q	PRRT26	11J	9.5-12.0	34.52	13.58	18.5	BLK	-
	37X11.50R20LT	10PR 128Q	PRRT49	9J	7.5-10.0	36.52	11.42	16.5	BLK	-
	37X12.50R20LT	12PR 128Q	PRRT25R	10J	8.5-11.0	36.52	12.50	18.5	BLK	-
	37X12.50R20LT	12PR 128Q	PRRT25	10J	8.5-11.0	36.52	12.50	18.5	BLK	-
	38X15.50R20LT	10PR 128Q	PRRT27	12 1/2J	11.0-14.0	37.52	15.54	18.5	RWL	-
	HL275/50R22	116H XL	PRRT28	8 1/2J	7.5-9.5	32.87	11.18	13.6	BLK	EV
	LT285/50R22	10PR 121/118Q	PRRT29	9J	8.5-10.0	33.27	11.69	16.5	BLK	-
LT285/55R22	10PR 124/121S	PRRT54	9J	8.5-10.0	34.37	11.69	16.5	BLK	EV	
LT305/55R22	10PR 122/119S	PRRT55	9 1/2J	9.0-11.0	35.24	12.44	16.5	BLK	EV	
33X12.50R22LT	10PR 109Q	PRRT31	10 1/2J	10.0-12.0	32.52	12.45	18.5	BLK	-	
33X12.50R22LT	12PR 114Q	PRRT32	10 1/2J	10.0-12.0	32.52	12.45	18.5	BLK	-	

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
22"	33X13.50R22LT	12PR 114Q	PRRT33	11J	10.5-12.0	32.52	13.58	18.5	BLK	-
	33X14.50R22LT	12PR 115Q	PRRT34	13J	12.5-14.0	32.52	15.16	18.5	BLK	-
	35X12.50R22LT	10PR 117Q	PRRT35	10J	8.5-11.0	34.52	12.50	18.5	BLK	-
	35X12.50R22LT	12PR 121Q	PRRT36	10J	8.5-11.0	34.52	12.50	18.5	BLK	-
	35X13.50R22LT	12PR 122Q	PRRT37	11J	10.5-12.0	34.52	13.58	18.5	BLK	-
24"	285/40R24	112H XL	PRRT38	10J	9.5-11.0	32.99	11.42	13.6	BLK	-
	LT295/45R24	10PR 120/117R	PRRT56	10J	9.5-11.0	34.49	11.65	16.5	BLK	-
	33X13.50R24LT	12PR 113Q	PRRT39	12J	11.5-12.5	32.52	13.58	18.5	BLK	-
	33X14.50R24LT	12PR 118Q	PRRT40	13J	12.5-14.0	32.52	13.44	18.5	BLK	-
	35X13.50R24LT	12PR 116Q	PRRT41	12J	11.5-13.5	34.52	13.44	18.5	BLK	-
	35X14.50R24LT	10PR 118Q	PRRT42	13J	12.5-14.0	34.52	14.46	18.5	BLK	-
35X15.50R24LT	12PR 117Q	PRRT43	14J	13.0-15.5	34.52	15.52	18.5	BLK	-	
26"	305/30R26	109H XL	PRRT44	11J	10.5-11.5	33.23	12.32	13.6	BLK	-
	LT305/35R26	10PR 108/104Q	PRRT48	11J	10.0-12.0	34.41	12.32	16.5	BLK	-

*Every effort has been made to verify the accuracy of the listed information. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



Control any driving situation with the New Mutant X-AT all-terrain tire, designed for a perfect blend of on- and off-road performance. It is one of the most aggressive all-terrain tread designs available, with advanced tread compound and deep siping that delivers superior traction in mud, snow, and loose gravel, all while maintaining smooth handling and a comfortable ride on pavement.

The New Mutant X-AT features a unique dual sidewall design for enhanced strength and puncture resistance on challenging trails. The innovative tread pattern with an intermediate void ratio and uniform squared shoulder blocks maximizes your contact patch for confident on-road handling without sacrificing off-road capability. This optimized design also reduces road noise for a quieter driving experience.

Whether you're navigating city streets or venturing off the beaten path, the X-AT all-terrain tire is your perfect companion for the journey ahead.





NEW MUTANT X-AT

All-Terrain Tire



- ROAD HAZARD
- 3PLY
- 50K MILEAGE
- 4 YEARS WARRANTY
- FULL TREAD DEPTH
- SILICON
-

- **Advanced All-Terrain Tread Compound:** This new silica tread compound delivers a perfect balance of extended tread life and improved traction on both paved and unpaved surfaces.
- **Deep, Multi-Functional Grooves and Siping:** These features enhance traction in a wide variety of road conditions, including wet, dry, and off-road environments.
- **Staggered Shoulder Lugs:** The lugs offer a biting edge for superior grip on rocky terrain.
- **Wider Contact Patch:** This design provides increased handling stability for both on-road and off-road driving.
- **Advanced "X" Tread Pattern with Pitch Variation:** This design reduces road noise for a quieter highway ride, enhancing comfort for drivers and passengers.
- **Aggressive "SPIKE" X-AT Dual Sidewall Design:** This design not only delivers additional off-road traction and sidewall protection but also offers drivers a unique visual customization option.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	LT235/75R15	6PR 104/101S	NPRXATS1	6 1/2J	6.0-8.0	28.86	9.25	15.1	BLK	Y
	245/70R16	111T XL	NPRXATS4	7J	6.5-8.0	29.53	9.76	12.1	BLK	Y
	265/70R16	112T	NPRXATS5	8J	7.0-9.0	30.63	10.71	12.1	BLK	Y
	265/75R16	116T	NPRXATS6	7 1/2J	7.0-9.0	31.65	10.51	12.1	BLK	Y
	LT225/75R16	10PR 115/112S	NPRXATS2	6J	6.0-7.5	29.29	8.78	15.1	BLK	Y
16"	LT235/85R16	10PR 120/116S	NPRXATS3	6 1/2J	6.0-7.5	31.73	9.25	15.1	BLK	Y
	LT265/75R16	10PR 123/120R	NPRXAT01	7 1/2J	7.0-9.0	31.65	10.51	15.1	BLK	Y
	LT285/75R16	10PR 126/123R	NPRXAT02	8J	7.5-9.5	32.83	11.26	15.1	BLK	Y
	245/65R17	111T XL	NPRXATS8	7J	7.0-8.5	29.53	9.76	12.1	BLK	Y
	265/65R17	112T	NPRXATS11	8J	7.5-9.5	30.55	10.71	12.1	BLK	Y
17"	265/70R17	115S	PRXAT03SF	8J	7.0-9.0	31.65	10.71	12.1	BLK	Y
	LT235/80R17	10PR 120/117S	NPRXATS7	6 1/2J	6.0-8.0	31.81	9.25	15.1	BLK	Y
	LT245/70R17	10PR 119/116S	NPRXATS9	7J	6.5-8.0	30.55	9.76	15.1	BLK	Y
	LT245/75R17	10PR 121/118S	NPRXATS10	7J	6.5-8.0	31.50	9.76	15.1	BLK	Y
	LT265/65R17	10PR 120/117S	NPRXAT05	8J	8.0-9.5	30.55	10.71	15.1	BLK	Y
	LT265/70R17	10PR 121/118Q	PRXAT04SF	8J	7.0-9.0	31.65	10.71	15.1	BLK	Y
	LT285/70R17	10PR 121/118Q	PRXAT06SF	8 1/2J	7.5-9.5	32.76	11.50	15.1	BLK	Y
	33X12.50R17LT	10PR 120Q	PRXAT08SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	35X10.50R17LT	10PR 121R	PRXAT09SF	8 1/2J	7.0-9.0	34.52	10.54	15.1	BLK	Y
	35X11.50R17LT	10PR 128Q	PRXAT68	9J	7.5-10.0	34.52	11.42	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
17"	35X12.50R17 LT	10PR 121R	PRXAT10SF	10J	8.0-10.5	34.52	12.50	15.1	BLK	Y
	37X12.50R17LT	12PR 128Q	PRXAT66	10J	8.0-10.5	36.52	12.50	15.1	BLK	Y
18"	235/60R18	107H XL	NPRXATS12	7J	6.5-8.5	29.09	9.45	12.1	BLK	Y
	245/60R18	109H XL	NPRXATS13	7J	7.0-8.5	29.57	9.76	12.1	BLK	Y
	265/60R18	114T XL	NPRXATS14	8J	7.5-9.5	30.51	10.71	12.1	BLK	Y
	265/65R18	116T XL	NPRXATS15	8J	7.5-9.5	31.54	10.71	12.1	BLK	Y
	275/65R18	116T	NPRXATS16	8J	7.5-9.5	32.09	10.98	12.1	BLK	Y
	LT265/60R18	10PR 119/116R	NPRXAT11	8J	8.0-9.5	30.51	10.71	15.1	BLK	Y
	LT265/70R18	10PR 124/121S	NPRXATS17	8J	7.0-9.0	32.64	10.71	15.1	BLK	Y
	LT275/70R18	10PR 125/122R	PRXAT12SF	8J	7.0-9.0	33.19	10.98	15.1	BLK	Y
	LT285/65R18	10PR 125/122R	PRXAT13SF	8 1/2J	8.5-10.0	32.56	11.50	15.1	BLK	Y
	33X12.50R18LT	10PR 118Q	PRXAT15SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
20"	35X12.50R18 LT	10PR 123R	PRXAT16SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	265/50R20	111H XL	PRXAT67	8 1/2J	7.5-9.5	30.47	10.91	12.1	BLK	Y
	275/55R20	117T XL	PRXAT17SF	8 1/2J	7.5-9.5	31.89	11.18	12.1	BLK	Y
	275/60R20	115T	PRXAT19SF	8J	7.5-9.5	32.99	10.98	12.1	BLK	Y
	LT275/55R20	10PR 120/117Q	PRXAT18SF	8 1/2J	8.0-9.5	31.89	11.18	15.1	BLK	Y
	LT275/60R20	10PR 123/120R	NPRXAT20	8J	8.0-9.5	32.99	10.98	15.1	BLK	Y
	LT275/65R20	10PR 126/123R	NPRXAT21	8J	8.0-9.5	34.09	10.98	15.1	BLK	Y
	LT285/55R20	10PR 122/119Q	PRXAT22SF	9J	8.5-10.0	32.36	11.69	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	LT285/60R20	10PR 125/122R	PRXAT60	8 1/2J	8.5-10.0	33.46	11.50	15.1	BLK	Y
	LT285/65R20	10PR 127/124R	NPRXATS18	8 1/2J	8.5-10.0	34.57	11.50	15.1	BLK	Y
	LT295/60R20	10PR 126/123S	PRXAT61	8 1/2J	8.5-10.5	33.94	11.77	15.1	BLK	Y
	LT295/65R20	10PR 129/126P	PRXAT62	8 1/2J	8.5-10.5	35.12	11.77	15.1	BLK	Y
	33X11.50R20LT	10PR 118Q	PRXAT23SF	9J	8.0-10.5	32.52	11.42	15.1	BLK	Y
	33X12.50R20LT	10PR 114Q	PRXAT25SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	33X12.50R20LT	12PR 119Q	PRXAT26SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	35X11.50R20LT	10PR 124R	NPRXAT24	9J	8.0-10.5	34.52	11.42	15.1	BLK	Y
	35X12.50R20LT	10PR 121Q	PRXAT27SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	35X12.50R20LT	12PR 125Q	PRXAT28SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
22"	37X12.50R20LT	12PR 128Q	PRXAT63	10J	8.5-11.0	36.52	12.50	15.1	BLK	Y
	37X13.50R20 LT	12PR 128Q	PRXAT29SF	11J	9.5-12.0	36.52	13.58	15.1	BLK	Y
	285/45R22	114T XL	PRXAT30SF	9 1/2J	9.0-10.5	32.09	11.22	12.1	BLK	Y
	305/40R22	114H XL	NPRXAT31	11J	10.0-12.0	31.61	12.32	12.1	BLK	Y
	LT285/55R22	10PR 124/121S	PRXAT69	9J	8.5-10.0	34.37	11.69	15.1	BLK	Y
	33X12.50R22LT	10PR 109R	PRXAT32SF	10J	10.0-12.0	32.52	12.45	15.1	BLK	Y
	33X12.50R22LT	12PR 114Q	PRXAT33SF	10J	10.0-12.0	32.52	12.45	15.1	BLK	Y
	35X12.50R22LT	10PR 117R	PRXAT34SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	35X12.50R22LT	12PR 121Q	PRXAT35SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	37X13.50R22 LT	12PR 128Q	PRXAT36SF	11J	9.5-12.0	36.52	13.58	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
24"	33X12.50R24 LT	12PR 106Q	PRXAT64	11 1/2J	10.5-12.5	32.52	12.60	15.1	BLK	Y
	33X13.50R24 LT	12PR 113Q	PRXAT37SF	12 1/2J	11.5-12.5	32.52	13.58	15.1	BLK	Y
	35X12.50R24LT	12PR 116Q	PRXAT65SF	10 1/2J	10.0-12.0	34.52	12.45	15.1	BLK	Y
	35X13.50R24LT	12PR 116Q	PRXAT38SF	12J	11.5-13.5	34.52	13.44	15.1	BLK	Y
	37X13.50R24LT	12PR 124Q	PRXAT39SF	11J	9.5-12.0	36.52	13.58	15.1	BLK	Y
26"	35X12.50R26LT	12PR 115Q	PRXAT42SF	11 1/2J	11.0-12.0	34.52	12.45	15.1	BLK	Y
	37X12.50R26LT	12PR 117Q	PRXAT43SF	10 J	9.5-11.5	36.52	12.50	15.1	BLK	Y
	37X13.50R26LT	12PR 117Q	PRXAT40SF	11J	10.5-13.0	36.52	13.44	15.1	BLK	Y



*Every effort has been made to verify the accuracy of the listed information. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

Brave the winter with confidence with the New Mutant Arctic, which is a studdable winter tire designed specifically for light trucks and SUVs. It delivers confidence-inspiring performance in harsh winter conditions.

The New Mutant Arctic features a directional tread design, a winter-optimized tread compound, and industry-leading construction techniques. This combination ensures excellent traction, improved braking, and superior hydroplaning resistance, even in severe winter weather.



NEW MUTANT ARCTIC

Light Truck Winter Tire



Off-Road Performance



Dry Performance



Ride Comfort



*Ratings are on a scale of 1-10



Wet Performance



Winter Performance



Quiet Ride



- Superior winter tread compound delivers improved traction and balanced handling in winter conditions.
- Wide circumferential grooves channel snow and evacuate water and slush for enhanced hydroplaning resistance.
- Increased sipe density and interlocking ripple design create more biting edges for controlled handling on ice and snow.
- Large, squared-off shoulder blocks provide a wider contact patch for greater stability and handling.
- Studdable with seven rows of pin holes across the contact patch for the ultimate traction on ice and compacted snow.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	235/65R16C	10PR 121/119R	PNMICE01	7J	6.5-7.5	28.03	9.45	16.0	BLK	Y
	LT225/75R16	10PR 115/112Q	PNMICE02	6J	6.0-7.5	29.29	8.78	16.0	BLK	Y
	LT245/75R16	10PR 120/116R	PNMICE03	7J	6.5-8.0	30.47	9.76	16.0	BLK	Y
17"	265/70R17	116T XL	PNMICE21	8J	7.0-9.0	31.65	10.71	12.6	BLK	Y
	LT245/75R17	10PR 121/118Q	PNMICE05	7J	6.5-8.0	31.5	9.76	16.0	BLK	Y
	LT265/70R17	10PR 123/120Q	PNMICE06	8J	7.0-9.0	31.65	10.71	16.0	BLK	Y
	LT285/70R17	10PR 126/123Q	PNMICE04	8 1/2J	7.5-9.5	32.76	11.50	16.0	BLK	Y
	33X12.50R17LT	10PR 120R	PNMICE14	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
	35X12.50R17LT	10PR 125R	PNMICE15	10J	8.0-10.5	34.52	12.50	16.0	BLK	Y
	37X12.50R17LT	10PR 128Q	PNMICE25	10J	8.0-10.5	36.52	12.50	16.0	BLK	Y
18"	275/65R18	116T XL	PNMICE22	8J	7.5-9.5	32.09	10.98	12.6	BLK	Y
	LT275/65R18	10PR 123/120R	PNMICE08	8J	8.0-9.5	32.09	10.98	16.0	BLK	Y
	LT275/70R18	10PR 125/122R	PNMICE07	8J	7.0-9.0	33.19	10.98	16.0	BLK	Y
	LT285/65R18	10PR 125/122R	PNMICE20	8 1/2J	8.5-10.0	32.56	11.50	12.6	BLK	Y
	33X12.50R18LT	10PR 118R	PNMICE16	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
	35X12.50R18LT	10PR 123R	PNMICE17	10J	8.5-11.0	34.52	12.50	16.0	BLK	Y
20"	275/55R20	117T XL	PNMICE23	8 1/2J	7.5-9.5	31.89	11.18	12.6	BLK	Y
	275/60R20	115T	PNMICE10	8J	7.5-9.5	32.99	10.98	12.6	BLK	Y
	LT275/65R20	10PR 126/123R	PNMICE11	8J	8.0-9.5	34.09	10.98	16.0	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	33X12.50R20LT	10PR 114R	PNMICE12	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
	35X12.50R20LT	10PR 121R	PNMICE13	10J	8.5-11.0	34.52	12.50	16.0	BLK	Y
22"	275/50R22	115T XL	PNMICE24	8 1/2J	7.5-9.5	32.87	11.18	12.6	BLK	Y
	285/45R22	114T XL	PNMICE09	9 1/2J	9.0-10.5	32.08	11.22	12.6	BLK	Y
	33X12.50R22LT	10PR 109R	PNMICE18	10 1/2J	10.0-12.0	32.52	12.45	16.0	BLK	Y
	35X12.50R22LT	10PR 117R	PNMICE19	10J	8.5-11.0	34.52	12.50	16.0	BLK	Y



*Every effort has been made to verify the accuracy of the listed information.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

Built for discerning drivers, the all-new Predator Comptrax PR1 A/S ultra high performance tire seamlessly blends cutting-edge design with uncompromising performance for crisp handling and comfort across all seasons.

Featuring a striking aesthetic, advanced tread design, and innovative tire compound, the Comptrax PR1 A/S delivers confident control, elevating your driving experience in a way that embodies our brand's relentless pursuit of performance. The Comptrax PR1 A/S carves through corners with precision, while maintaining a luxuriously quiet ride. Backed by a 40,000-mile warranty and a full year of road hazard protection, this all-season performer offers miles of confidence and sculpted style for your car, crossover, truck, or SUV.

Comptrax PR1 A/S

All-Season Ultra High Performance



Dry Performance



9.0



Wet Performance



8.0



Winter Performance



5.0



Ride Comfort



8.0



Quiet Ride



9.0

*Ratings are on a scale of 1-10

- Three main grooves work together with curved lateral channels to efficiently evacuate water, helping maintain contact with the road in wet weather.

- Deep sipes along the inner shoulder tread blocks and central tread blocks improve water evacuation on wet roads and interlock during cornering, providing enhanced dry traction and improved braking performance.

- A solid circumferential rib positioned next to the outer shoulder blocks enhances responsive handling and increases straight-line stability.

- Ranging from 16-inch to 24-inch applications, the Predator Comptrax PR1 A/S is available in 37 sizes with more on the way.



WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
16"	205/55ZR16	91W	PDCPAS01	6 1/2J	5.5 - 7.5	24.88	8.43	10.0	BLK
	215/45ZR17	91W XL	PDCPAS03	7J	7.0 - 8.0	24.65	8.39	10.0	BLK
17"	215/55R17	94V	PDCPAS05	7J	6.0 - 7.5	26.30	8.90	10.0	BLK
	225/50ZR17	98W XL	PDCPAS07	7J	6.0 - 8.0	25.91	9.17	10.0	BLK
18"	225/55R17	101V XL	PDCPAS08	7J	6.0 - 8.0	26.77	9.17	10.0	BLK
	235/45R18	98V XL	PDCPAS14	8J	7.5 - 9.0	26.34	9.29	10.0	BLK
18"	235/50ZR18	101W XL	PDCPAS15	7 1/2J	6.5 - 8.5	27.28	9.65	10.0	BLK
	235/55R18	104V XL	PDCPAS16	7 1/2J	6.5 - 8.5	28.15	9.65	10.0	BLK
19"	245/45ZR18	100W XL	PDCPAS18	8J	7.5 - 9.0	26.65	9.57	10.0	BLK
	235/40ZR19	96W XL	PDCPAS21	8 1/2J	8.0 - 9.5	26.42	9.49	10.0	BLK
19"	245/40ZR19	98W XL	PDCPAS24	8 1/2J	8.0 - 9.5	26.73	9.76	10.0	BLK
	245/35ZR20	95W XL	PDCPAS26	8 1/2J	8.0 - 9.5	26.77	9.76	10.0	BLK
20"	245/40ZR20	99W XL	PDCPAS27	8 1/2J	8.0 - 9.5	27.72	9.76	10.0	BLK
	245/45ZR20	103W XL	PDCPAS28	8J	7.5 - 9.0	28.66	9.57	10.0	BLK
22"	275/40ZR20	106W XL	PDCPAS29	9 1/2J	9.0 - 11.0	28.66	10.94	10.0	BLK
	265/35ZR22	102W XL	PDCPAS31	9 1/2J	9.0 - 10.5	29.33	10.67	10.0	BLK
24"	305/40R22	114V XL	PDCPAS33	11J	10.0 - 12.0	31.61	12.32	10.0	BLK
	305/35R24	112V XL	PDCPAS37	11J	10.0 - 12.0	32.44	12.32	10.0	BLK

*Every effort has been made to verify the accuracy of the listed information.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



Comptrax PRI SPORT

Ultra-High Performance Summer Tire

The Comptrax PRI Sport is an ultra-high performance summer tire built for drivers who want responsive handling, strong dry traction, and a confident feel behind the wheel. Offered in a wide range of sizes from 13 to 18 inches, it fits everything from compact daily drivers to sport compact and performance sedan applications. Its aggressive directional tread pattern, reinforced shoulder design, and performance-focused construction create a modern, track-inspired look with strong on-road capability.



Dry Performance



9.5



Wet Performance



8.0



Winter Performance



3.0



Ride Comfort



9.0



Quiet Ride



9.0

*Ratings are on a scale of 1-10

- Directional tread pattern designed to support precise steering and stable cornering.

- Reinforced outer shoulder blocks help improve grip during spirited driving.

- Central rib structure promotes straight-line stability and responsive handling.

- Wide circumferential grooves assist with water evacuation and wet-road confidence.

- Broad size coverage from 13 to 18 inches, including select XL fitments for performance applications.

- M+S rated for added versatility in changing road conditions.



WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
13"	165/70R13	79T	PDCGSPT01	5J	4.0-5.5	562	170	8.8	BLK
	175/70R13	82H	PDCGSPT02	5J	4.5-6.0	576	177	8.8	BLK
	185/70R13	86T	PDCGSPT03	5 1/2J	4.5-6.0	590	189	8.8	BLK
14"	165/70R14	81T	PDCGSPT04	5J	4.0-5.5	588	170	8.8	BLK
	175/65R14	82H	PDCGSPT05	5J	5.0-6.0	584	177	8.8	BLK
	175/70R14	84H	PDCGSPT06	5J	4.5-6.0	602	177	8.8	BLK
	185/60R14	82H	PDCGSPT07	5 1/2J	5.0-6.5	578	189	8.8	BLK
	185/65R14	86H	PDCGSPT08	5 1/2J	5.0-6.5	596	189	8.8	BLK
14"	185/70R14	88T	PDCGSPT09	5 1/2J	4.5-6.0	616	189	8.8	BLK

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
15"	175/60R15	81H	PDCGSPT10	5J	5.0-6.0	591	177	8.8	BLK
	185/60R15	84H	PDCGSPT11	5 1/2J	5.0-6.5	603	189	9.1	BLK
	185/65R15	88H	PDCGSPT12	5 1/2J	5.0-6.5	621	189	9.1	BLK
	195/65R15	91V	PDCGSPT13	6J	5.5-7.0	610	201	9.4	BLK
	205/60R15	91V	PDCGSPT14	6J	5.5-7.5	627	209	9.4	BLK
16"	185/55R16	83V	PDCGSPT15	6J	5.0-6.5	610	194	9.2	BLK
	195/55R16	87H	PDCGSPT16	6J	5.5-7.0	620	201	9.4	BLK
	205/55R16	91V	PDCGSPT17	6 1/2J	5.5-7.5	632	214	8.8	BLK
	205/60R16	92V	PDCGSPT18	6J	5.5-7.5	652	209	9.4	BLK
	215/60R16	95V	PDCGSPT19	6 1/2J	6.0-7.5	664	221	9.4	BLK
17"	205/55ZR17	95W XL	PDCGSPT20	6 1/2J	5.5-7.5	658	214	9.2	BLK
	215/55ZR17	98W XL	PDCGSPT21	7J	6.0-7.5	668	226	9.2	BLK
	225/45ZR17	94W XL	PDCGSPT22	7 1/2J	7.0-8.5	634	225	8.8	BLK
18"	215/45ZR18	93W XL	PDCGSPT23	7J	7.0-8.0	651	213	8.8	BLK
	215/50R18	92V	PDCGSPT24	7J	6.0-7.5	673	226	8.8	BLK
	215/55R18	95V	PDCGSPT25	7J	6.0-7.5	693	226	9.2	BLK
	225/40ZR18	92W XL	PDCGSPT26	8J	7.5-9.0	637	230	8.8	BLK
	225/45ZR18	95W XL	PDCGSPT27	7 1/2J	7.0-8.5	659	225	8.8	BLK
	235/45ZR18	94W	PDCGSPT28	8J	7.5-9.0	669	236	8.8	BLK

*Every effort has been made to verify the accuracy of the listed information.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

BOULEVARD G/T

All-Season Touring Tire

The Boulevard G/T is an all-season touring tire made for drivers who want the authentic heritage styling of classic American performance tires while delivering the versatility drivers expect today. Available in sizes from 13 to 15 inches, it fits a wide range of vintage and retro-performance applications while maintaining a period-correct look. With its traditional tread design, available large White Wall (WW) or Raised White Letter (RWL) sidewalls, and updated construction details, the Boulevard G/T delivers the look of a heritage tire with the confidence of modern engineering. It is also M+S rated for added versatility in changing road conditions.



Dry Performance



7.5



Wet Performance



7.0



Winter Performance



4.0



Ride Comfort



8.5



Quiet Ride



8.0

*Ratings are on a scale of 1-10

- Traditional all-season touring tread pattern designed for reliable year-round driving.
- Classic profile that complements vintage and muscle-car applications.
- Available with large White Wall (WW) or Raised White Letter (RWL) sidewalls.
- Modern tire compound helps improve grip and wear performance.
- Engineered internal construction promotes stability, ride comfort, and consistent handling.
- M+S rated for added versatility in varied weather conditions.



WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
13"	155/80R13	79S	PDBVGT05W	4.50B	4.0-5.0	22.76	6.18	10.1	WSW
	175/70R14	84S	PDBVGT04W	5J	4.5-6.0	23.70	6.97	10.1	WSW
14"	235/60R14	96H	PDBVGT11R	7J	6.5-8.5	25.12	9.45	10.1	RWL
	165R15	86H	PDBVGT07W	4 1/2J	4.0-5.0	25.43	6.57	9.1	WSW
15"	235/70R15	106S XL	PDBVGT13R	7J	6.0-8.0	27.99	9.45	10.1	RWL
	275/60R15	107T	PDBVGT02R	8J	7.5-9.5	27.99	10.98	10.1	RWL

*Every effort has been made to verify the accuracy of the listed information. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





STEEL PAYLOAD

Predator All Steel ST



Dry Performance



- Advanced all-steel belt construction for improved durability and increased payload.



Wet Performance



- Patented polymer tread compound lowers rolling resistance, helping improve fuel economy and tread life.



Winter Performance



- Four circumferential grooves channel and disperse water and slushy snow to prevent hydroplaning.



Ride Comfort



- Symmetrical ribbed tread design delivers directional stability, driving smoothness and low rolling resistance.



Quiet Ride



- Enhanced sidewall ribs to prevent curbing damage on the tire casing.
- Improved tread profile for a wider tire stance for better weight distribution, promoting even tire wear and increased tread life.

*Ratings are on a scale of 1-10

The Predator All Steel ST is a durable all-steel radial construction highway trailer tire for heavy-duty hauling applications. The combination of a newly formulated tread compound and advanced tire carcass design achieves low rolling resistance and extended service life, making fleets maximize fuel efficiency and lower total cost of ownership.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
15"	ST205/90R15	G/14PR 125/120L	PTST02	5 1/2J	5.0-6.5	29.53	7.99	9.57	BLK
	ST225/75R15	F/12PR 121/117M	PTST03	6J	6.0-7.5	28.31	8.78	10.2	BLK
	ST225/75R15	G/14PR 123/119L	PTST04	6J	6.0-7.5	28.31	8.78	10.2	BLK
16"	ST235/80R16	G/14PR 129/125M	PTST05	6 1/2J	6.0-8.0	30.79	9.25	9.57	BLK
	ST235/80R16	H/16PR 130/126L	PTST06	6 1/2J	6.0-8.0	30.79	9.25	9.57	BLK
	ST235/85R16	G/14PR 132/127M	PTST07	6 1/2J	6.0-7.5	31.73	9.25	11.46	BLK
	ST235/85R16	H/16PR 133/128L	PTST08	6 1/2J	6.0-7.5	31.73	9.25	11.46	BLK

*Every effort has been made to verify the accuracy of the listed information. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



PREDATOR TIRE LIMITED WARRANTY

STANDARD COVERAGE

If your PREDATOR TIRES becomes unserviceable as a result of an eligible adjustable condition during the first 10% of tread life, the owner will be compensated 100% of the value of the tire. After that amount, PREDATOR TIRES will offer a prorated mileage credit, down to 25% remaining tread depth, towards purchasing a comparable PREDATOR TIRES brand tire. The owner must pay for mounting, balancing, and any other additional charges, such as taxes and freight. PREDATOR TIRES shall not be responsible for any other fees incurred as a part of any exchange, labor, or additional costs resulting from this guarantee. PREDATOR TIRES shall not be responsible for any damage or other issues caused by the improper installation (including any of the exclusions below), balancing, or selection of tire—including the selection of size, specification, type, or use of such tire (including those obligations under the "Owner's Obligations section below") that the manufacturer of your vehicle does not recommend. All terms and conditions of this guarantee are limited to the terms and conditions contained in this guarantee.

PREDATOR TIRES include the Standard Coverage and the additional coverages listed below.

MILEAGE WARRANTY

- 50,000 miles tread life warranty for New Mutant X-AT, New Mutant X-RT, ComPtrax PR1 Sport, ComPtrax PR1 A/S 22-inch and smaller, and 13.5-inch wide or less.
- 55,000 miles tread life warranty for New Mutant RT Trail and RT Trail EV 22-inch and smaller, and 13.5-inch wide or less.
- For any PREDATOR TIRES marketed and sold as an all-terrain, rugged-terrain, or mud-terrain tire not listed above, a 50,000-mile tread life warranty applies for 22-inch and smaller sizes and 13.5-inch wide or less, unless otherwise specified at the time of product launch.
- Vehicles with staggered fitments, where the front and rear tires have different tire sizes, cannot be rotated. PREDATOR TIRES warrants tires mounted on the rear axle of vehicles with staggered fitments only up to 50% of the warranted miles under our standard mileage warranty for all applicable tire models, tread patterns, and tire sizes listed in this warranty.

PREDATOR TIRES are warrantied against treadwear prior to the applicable indicated mileage for each specific tire model and size, provided that you:

1. Rotate your tires following the prescribed rotation patterns at least every 3,500 miles or less (UHP passenger car tires) or 5,000 miles or less (standard light truck tires) and have documentation showing the rotation schedule.

2. The TIRE SERVICE RECORD form filled out by the tire shop, dealer, or service department during regular routine maintenance. The required TIRE SERVICE RECORD form can be downloaded here <https://www.predatortires.com/uploads/pdf/Predator-TireServiceRecord.pdf> or at the bottom of this page.
3. Present the subject tire for adjustment during regular routine maintenance.
4. Present documentation showing the rotation schedule when requesting an adjustment and the date of purchase, vehicle type, model, odometer reading, and tire pressure.

When the tread becomes worn to 2/32nd inch (shown by tread wear indicators molded into the tread grooves), the tire tread shall be considered worn. The Department of Transportation specifications determine such tread wear, and in accordance with applicable laws and regulations.

4-YEAR MANUFACTURER WARRANTY

The 4-Year Manufacturer Warranty is a non-prorated replacement for any manufacturing defects in material and workmanship under normal and intended use. Non-intended uses include racing, sanctioned off-road competition, or other competitive activities. For any PREDATOR TIRES marketed and sold as an all-terrain, rugged-terrain, or mud-terrain tire, recreational off-road use on unpaved terrain is considered normal intended use and is covered under this warranty. If a manufacturing defect in material or workmanship occurs, the tire will be replaced at no charge, on a non-prorated basis to the consumer.

CONDITIONS AND EXCLUSIONS

PREDATOR TIRES warranties are limited to the original purchaser and the original vehicle on which they are installed, and such warranties and guarantees are not assignable to subsequent purchasers or vehicles. All warranties and guarantees by PREDATOR TIRES are only applicable in the United States and Canada. This warranty does not cover any tires used or equipped on a vehicle registered or operated outside the United States and Canada.

The Limited Warranty does NOT cover the following:

- Tire branded or marked "blem," "Non-Adjustable (N/A)," or previously adjusted.
- Failure, damage, or irregular wear due to:
 - Road hazards (i.e., punctures, cuts, snags, bruises, impact breaks, etc.), wreck or collision.
 - Fire, accident, or vandalism.
 - Mechanical condition of the vehicle, including misalignment, wheel imbalance, faulty shocks or brakes.
 - Misapplication of tire or use of improper inner tube.
 - Alteration of the tire or addition of foreign material.
 - Use of tire chains, tire spinning, racing, or other competitive activities.
 - Off-road use, except for any PREDATOR TIRES marketed and sold as an all-terrain, rugged-terrain, or mud-terrain tire, for which recreational off-road use on unpaved terrain is considered normal intended use and is not an exclusion under this warranty.
- Non-factory vehicle staggered tire fitments.
- Costs of mounting and balancing service.
- Costs related to tire pressure monitoring systems.
- Costs related to shipping and transportation of the tire.
- Loss of time or use, inconvenience, or any incidental or consequential damages.

- Improper use or operation including, but not limited to: improper tire and vehicle maintenance, running flat or run with severe underinflation, misuse, abuse, accident fire or chemical corrosion, underinflation, overinflation, overloading, over deflection, or failure to follow recommended rotation practices.
- Improper installation, improper mounting or dismounting, misapplication, improper repairs, wheel misalignment, or imbalance in the tire/wheel assembly.
- Tire size, load, and speed rating do not match the tire specifications outlined in your vehicle owner's manual.
- Tires with the Department of Transportation (DOT) number removed or rendered illegible; tires must bear the DOT prescribed tire identification numbers. Ride complaints after the first 1/32nd inch of tread wear or due to damaged wheels or any vehicle condition.

PREDATOR TIRES does not warrant any work performed by the dealer, including, but not limited to their selection, fitment, mounting and balancing, inspection, or repair of any tire.

INELIGIBLE TIRES

Tires are not eligible for warranty if:

- The mileage and tire rotation records are not available or verifiable.
- The subject tire or tires are worn beyond the tread wear bar indicators (less than 2/32nd inch of remaining tread).
- The subject tire or tires are not presented and available for inspection at an authorized dealer.
- Uniformity issues after the first 1/32nd inch of tread wear.

CONSUMER RIGHTS

This Limited Warranty gives you specific legal rights; you may also have other rights, which vary from state to state.

PREDATOR TIRES disclaims all other warranties, express or implied, including the implied warranty of merchantability, the implied warranty of fitness for a particular purpose and liability for incidental and consequential damages (i.e., loss of time, loss of use of vehicle, road services, towing charges, inconveniences, etc.).

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions may not apply to you.

NO ONE (including a PREDATOR TIRES employee, representative, or dealer) has the authority to vary the terms of this Limited Warranty.

OWNER'S OBLIGATION

When making a claim, you must return the tire to be replaced to your PREDATOR TIRES dealer and sign the customer signature section of the PREDATOR TIRES Claim Form.

Proper vehicle and tire care are necessary to obtain the expected wear from a tire. Therefore, it is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including:

1. Operating your tires at the inflation pressures recommended by the tire and vehicle manufacturer.
2. Keeping your tire and wheel assemblies in balance.

3. Proper wheel alignment.
4. Maintaining steering and suspension components to be within manufacturer specifications.
5. Rotating your tires at least every 3,500 miles or less (UHP passenger car tires) or 5,000 miles or less (standard light truck tires).

CLAIMS PROCESS

To make a claim under this Limited Warranty, you must:

1. Present your vehicle with the subject tires, the original copy of this Limited Warranty and the original sales invoice to an authorized PREDATOR TIRES dealer.
2. Present your completed Tire Service Record to the authorized PREDATOR TIRES dealer along with the other two documents in #1. For treadwear mileage warranty consideration, the Tire Service Record must show the times and places that the tire rotations were performed. PREDATOR TIRES recommends rotations at 3,500-mile intervals or less for high-performance passenger car tires and 5,000-mile intervals or less for standard light truck tires.
3. Complete and sign the PREDATOR TIRES Limited Warranty Claim form provided by the dealer, keep a copy for your records, and leave the tire with the dealer.
4. If you purchased the tire from an Internet or mail-order merchant, you will need to submit your claim, together with the dismantled tire, to that merchant. You are responsible for all of the costs of dismantling and shipping. Your claim will be administered in accordance with the Limited Warranty that was in effect when you purchased the tires.

FORMS (available for download on www.predatortires.com)

Limited Warranty : <https://www.predatortires.com/Warranty>

Tire Service Record : <https://www.predatortires.com/uploads/pdf/Predator-TireServiceRecord.pdf>

Limited Warranty Claim Form : <https://www.predatortires.com/uploads/pdf/Predator-LimitedWarrantyClaimForm.pdf>

CONTACT INFORMATION

PREDATOR TIRES TIRE
5118 Park Avenue, Suite 601
Memphis, TN 38117

We recommend that you have your PREDATOR TIRES tire dealer inspect your tires any time you notice irregular or uneven tread wear and rotate them, if necessary.

Failure to follow any of the above-mentioned Owner Obligations may be considered a breach of the warranty agreement and result in the termination of the warranty agreement. Furthermore, PREDATOR TIRES reserves the right to review each warranty claim and deny the warranty application based on failing to follow any of the above-mentioned Owner Obligations.

PREDATOR TIRES reserves the right to change the terms and conditions of all warranties at any time.

PREDATOR[®] Pursuit of Performance TIRES

@PREDATORTIRES

FOLLOW US



WWW.PREDATORTIRES.COM

[@PREDATORTIRES](https://www.instagram.com/PREDATORTIRES)

marketing@transamericatire.com

TRANSAMERICA TIRE CO., LTD.

5118 PARK AVE., SUITE 601, MEMPHIS, TN 38117

832-891-2821